



SOLAR SAFEGUARD INSTRUCTION MANUAL

The Solar SafeGuard sends out sound and vibration every 30 seconds to drive out harmful and destructive pests like moles, voles, mice, and snakes. One full charge will power the Solar SafeGuard for approximately one week without sunlight.

Specifications:

- Range: 8,500 ft²
- Dimensions: 14 ¾ in. x 6 ¼ in.
- Power Supply: Ni-MH 1.2V 600mAh cell
- Solar Energy Panel: 2 ⅝ in. x 3 ½ in.

Getting Started

1. **Charge the solar head in the sun for two full days prior to first use.**
2. Once the solar head has been charged, thread the wires from the aluminum tube up through the transparent connector tube and connect them to the cable from the solar head.
3. Gently fix the solar head to the end of the transparent connector tube. Softly slide and twist the pieces together. Do not use excessive force.
4. Insert the aluminum tube into the ground. Be careful not to use excessive force or the device can be damaged (**See Installation Guide**).

Installation Guide

For best results, installation of 2 Solar SafeGuards every 100 feet is recommended. In order to get the most effective coverage, avoid any obstruction and allow the sound waves to be emitted freely.

Check the state and consistency of the ground surface before inserting the Solar SafeGuard. Frozen soil, irrigated or waterlogged ground is not suitable for use and can damage the unit.

Dig a pilot hole into the soil before inserting the aluminum tube. The density of the soil can greatly alter the effectiveness of the device. The more solid the earth, the better the device will project sound throughout the area.

Charge the Solar SafeGuard for two full days prior to first use. Fully charged, it can supply enough power for the night hours. The LED light will automatically turn on at night, brightening your yard, while at the same time providing you with a safe and beautiful landscape.

Important Notes

1. Do not bury the device past the aluminum tube. The solar head and transparent tube should remain exposed approximately an inch below the transparent tube.
2. Do not use a hammer at any time during installation or assembly. Do not use excessive force as this can damage the device.
3. While the Solar Safeguard is weather resistant, remove it if the ground is likely to freeze or flood.

We're Here to Help

Toll Free: 1-800-657-8214 **Outside the US:** 1-541-245-4488 **Email:** customerservice@goodlifeinc.com